

Befestigungsblech für Bordnetzdose Fixing Bracket for Norm Outlet

Montagehinweise

Alle vom Motorrad gelösten Schrauben sind gemäß Herstellerangaben wieder zu montieren, oder mit von SW-MOTECH gelieferten Schrauben zu ersetzen. Falls nicht anderweitig definiert, diese Schrauben nach Tabelle anziehen.

M6	9,6 Nm
M8	23 Nm

Gegebenenfalls Schrauben mit flüssiger Schraubensicherung einkleben.

Prüfen Sie nach 50 km alle Verbindungen auf festen Sitz.

SW-MOTECH GmbH & Co. KG
Bahnhofstrasse 44d
35282 Rauschenberg
-Germany-

Tel.: ++ 49 (0) 6425 816 800
Fax: ++ 49 (0) 6425 816 810

www.sw-motech.com

Mounting Instructions

SW-MOTECH products should be installed by a qualified, experienced motorcycle technician. If you are unsure of your ability to properly install a product, please have the product installed by your local motorcycle dealer. SW-MOTECH takes no responsibility for damages caused by improper installation.

All screws, bolts and nuts, including all replacement hardware provided by SW-MOTECH, should be tightened to the torque specified in the OEM maintenance manual for your motorcycle. If no torque specifications are provided in the OEM maintenance manual, the following torques may be used:

M6	9,6 Nm
M8	23 Nm

All screws, bolts and nuts should be checked after driving the first 50 km to ensure that all are tightened to the proper torque.

Medium strength liquid thread-locker (i.e., "Locktite") should be used to secure all screws, bolts and nuts.

! Achtung: Schraubenlänge muss selbst ermittelt werden, da diese je nach Motorradtyp variieren.
Attention: The type of screw length may vary depending upon motorcycle.

1 Befestigungsblech Fixing Bracket



schwarz/black
CPA.00.006.001 02
Anzahl/ Pcs. 1

3 Innensechskant- schraube mit flachem Kopf Hexagon Socket Screw (short Head)



schwarz/black
M8 x 35 DIN 6912
Anzahl/ Pcs. 2

5 Innensechskant- schraube mit flachem Kopf Hexagon Socket Screw (short Head)



schwarz/black
M8 x 40 DIN 6912
Anzahl/ Pcs. 2

2 Distanzbuchse Spacer



Da:13 Di:8,4 h:10
Anzahl/ Pcs. 2

4 Unterlegscheibe Washer



schwarz/black
A 8,4 DIN 125
Anzahl/ Pcs. 2

6 Kappe für Innensechskantschraube Cap for Hexagon Socket Screw



schwarz/black
KEK.00.M8.ISK
Anzahl/ Pcs. 2

